GREATMATS SPECIALTY FLOORING

Tuff Seal Floor Tile Product Specifications

Material:	Made from selected post-industrial recycled PVC		
Size:	17.68" × 17.68" (450 mm x 450 mm)		
Coverage:	2.17 sq ft per tile		
Thickness:	1/4″ (6.5 mm)		
Weight per tile:	4.0 lb (1.8 kg)		
Weight per sq ft:	1.84 lbs (0.83 kg)		
Patterns:	Smooth, Stud, Marquis		
Colors:	Black, Brick Red, Butternut, Canvas, Caramel, Cerulean Blue, Chocolate,		
	Dark Gray, Evergreen, Light Gray, Meadow, Slate, Terracotta, White, Yellow		

Physical/Chemical Properties:

Tuff-Seal Tile meets or exceeds the requirements of ASTM F 1700 for Solid Vinyl Tile ASTM D 412 Breaking Load – 1653 psi; Static Load Limit-500 psi

Fire Resistance Properties:

ASTM E 648/NFPA 253 Critical Radiant Flux:	_Class 1
FMVSS 302:	Meets or exceeds
FAA Vertical Flammability:	_Meets or exceeds

Slip Resistance Properties:Meet	s or exceeds 0.6 for flat surfaces
---------------------------------	------------------------------------

Chemical Resistance Properties:

Chemical	Effect
Hydrochloric Acid 5%	No effect
Acetic Acid 5%	No effect
Isopropyl Alcohol 70%	No effect
Mineral Oil	No effect
Sodium Hydroxide 5%	No effect
Ammonia 5%	No effect
Bleach	No effect
Phenol 5%	No effect
Gasoline	No effect
Kerosene	No effect
Olive Oil	No effect
Motor Oil	No effect
Grease	No effect
Transmission Fluid	No effect
Brake Fluid	No effect
Sulfuric Acid	Moderate surface attack, slight color change

Greatmats.com 117 Industrial Ave Milltown, WI 54858 Toll free: 877-822-6622 Fax: 715-825-4928 info@greatmats.com