

GREATMATS

Equine Paver Tile 30 mm x 2x2 Ft.

Maintenance

It is the Specifier's responsibility to:

- Mandate covering and protection of floor from damage and construction debris until construction is complete.
- Assign to the appropriate party responsibility for the initial cleaning of floor following published procedures.

Greatmats recommends our environmentally friendly line of maintenance products, including ECleaner.

It is the General Contractor's responsibility to provide:

- A building or installation area that is fully enclosed from the elements, e.g., finished roof, windows, doors, etc.
- Temperature that is climate controlled with a minimum uniform temperature of 65° F for 48 hours prior to, during, and after the flooring installation, for acclimation of flooring materials.
- Protection for those areas of the flooring that are subject to direct sunlight through doors or windows by having the doors or windows covered for such time until the installation of the material is complete.
- Protection for flooring from damage and construction debris by using an appropriate floor covering until such time that the recommended initial cleaning may be performed

NOTE: Wash the paver tiles immediately after installation to reduce possibility of a slippery surface.

Indoor Maintenance	Cleaning Product	Mixture	Diluted Coverage	Equipment
Initial Cleaning	ECleaner	10 oz / gal. water	2,000 sq. ft. / gal.	Soft Nylon Brush or 3M 5100 Red Pad or Equal. vacuum up water
Daily Cleaning	-	-	-	Blow, vacuum or sweep loose debris
Periodic Cleaning	ECleaner	2-4 oz. / gal. water	4,000-6,000 sq. ft. / gal.	Soft Nylon Brush or 3M 5100 Red Pad or Equal. vacuum up water
Heavy Soil and Restorative Cleaning	Estrip	16 oz. / gal. water	1,000 sq. ft. / gal.	Soft Nylon Brush or 3M 5300 Blue, 7100 Brown, or 7200 Black pad as req'd. (Do not use High Productivity Pad). vacuum up water

Equine Paver Tile 30 mm x 2x2 Ft.

Maintenance – continued

Outdoor Maintenance	Cleaning Product	Mixture	Diluted Coverage	Equipment
Initial Cleaning	ECleaner	10 oz / gal. water	2,000 sq. ft. / gal.	Power wash, or scrub using soft Nylon Brush or 3M 5100 Red Pad on low-speed scrubber. Vacuum up water.
Daily Cleaning	-	-	-	Blow, vacuum or sweep loose debris
Periodic Cleaning	ECleaner	2-4 oz. / gal. water	4,000-6,000 sq. ft. / gal.	Hose wash, power wash, or scrub using soft Nylon Brush or 3M 5100 Red Pad on low-speed scrubber.
Heavy Soil and Restorative Cleaning	ECleaner, Estrip	16 oz. / gal. water	2,000 sq. ft. / gal. 1,000 sq. ft. / gal.	Power wash, or scrub using 3M Brown 7100 or Black 7200 pad as req'd. on low-speed scrubber. (Do not use High Productivity Pad).

CAUTION: Use all applicable PPE when using power washers. Use power washer at a suitable distance from the surface with the appropriate pressure and correct nozzle / spray pattern. Power washers can cause significant and permanent damage. Hire a professional if unsure regarding power washing safety or use.

Greatmats.com
 117 Industrial Ave
 Milltown, WI 54858
 Toll free: 877-822-6622
 Direct voice: 715-653-6100
 info@greatmats.com
 Revised 11/2023