



Slip Not 2000 Commercial Carpet Tile Case of 12

Product Specifications

SKU: SNXTILE-XX

Product Description			
Material	100% solution-dyed UV stabilized polypropylene fibers		
Backing	High density Bitumen waterproof rubber		
Tile Size	19-11/16 inches x 19-11/16 inches x 1/2 inch thick		
Case Pak	12 tiles per case - 32.4 sq. ft. per case		
Limited Warranty	3 years		
Technical Specifications			
Product Dimensions	Test	Requirement	Berber
Pile height	ISO 1776	In inches	3/16"
Total height	ISO 1776	In inches	1/2"
Pile weight	ISO 8543	In ounces per sq yd	54.56 oz/sq yd
Total weight	ISO 8543	In ounces per sq yd	152.18 oz/sq yd
Safety			
Surface Flammability	ASTM D2859 CPSC FF 1-70	Test specimen must be greater than 1" in at least 7 of 8 specimens tested	Passes
Performance			
Static electrical propensity	EN 1815	Antistatic: less than 2 kilovolts (kV)	< 2 kV
Static coefficient of friction	ASTM C1028	Slip coefficient: OSHA min. 0.5; ADA (guideline) min. 0.6	Wet: 0.6; Dry: 0.61
Color Fastness			
Color Fastness - water	ISO 105 E01	1 = considerable change; 6 = negligible or no change	5
Color Fastness - light	ISO 105 B02	1 = considerable change; 6 = negligible or no change	5
Color Fastness - to shampoo	ISO 1006	1 = considerable change; 6 = negligible or no change	5
To rubbing wet and dry	ISO 105 x 12	1 = considerable change; 6 = negligible or no change	Wet: 4; Dry: 4

Greatmats.com
117 Industrial Ave
Milltown WI 54858

Toll free: 877-822-6622
Direct voice: 715-653-6100
Fax: 715-825-4928

info@greatmats.com
2/2025