



# Performance Beast Plus Rubber Rolls

## Product Specifications

Roll Size: 4 x 25 feet

Roll Thickness: 14.5 mm total: 12mm vulcanized Composition Rubber base layer plus 2.5 mm Vulcanized Composition Rubber Surface Wear Layer

Roll Weight: 350 lbs

Standard Colors: Blue Premium, Dark Gray Premium, Mocha Latte 2, Steel Appeal 2

Premium Colors: Medium Grey Premium, Charcoal Premium, Dark Taupe Premium, Warm Grey Premium

Supreme Colors: Navy Premium, Green Premium, Maroon Premium, Red Premium

Material: High quality post-consumer recycled rubber granules encapsulated in a wear and water-resistant elastomeric network with a fusion bonded reprocessed EPDM surface wear layer.

| Performance Criteria                      | Test Method         | Typical Results                |
|---|---------------------|--------------------------------|
| Static Load Limit                         | ASTM F970 @ 250 PSI | 0.008"                         |
| Slip Resistance / Coefficient of Friction | ASTM D2047          | >0.90                          |
| VOC's / FloorScore / CHPS / CA 01350      | ASTM D5116          | Pass                           |
| Color Stability                           | ASTM F1515          | Good                           |
| Chemical Resistance                       | ASTM F925           | Good                           |
| Abrasion Resistance                       | ASTM D3389          | <1g, 1000 cycle                |
| Resistance to Light by Color Change       | ASTM F1515          | Pass                           |
| Resistance to Heat by Color Change        | ASTM F1514          | Pass                           |
| Flammability – Critical Radiant Flux      | ASTM E648           | Class II                       |
| Flammability – Pill Test                  | ASTM D2859          | Pass                           |
| Force Reduction                           | Deltec              | 17.40%                         |
| Energy Restitution                        | Deltec              | 66.30%                         |
| Vertical Deflection / Deformation         | ASTM F2772          | 0.6 mm                         |
| Surface Effect Slip Resistance            | ASTM F2772          | 93 BPV                         |
| Vertical Ball Rebound                     | ASTM F2772          | 97.1%                          |
| Force Reduction                           | ASTM F2772          | 12.6                           |
| Impact Insulation Class (IIC)             | ASTM E492           | 55                             |
| Sound Transmission Class (STC)            | ASTM E90            | 53                             |
| Delta IIC                                 | ASTM E2179          | 25                             |
| Sheet Dimension                           | Manufacturer        | 4' wide x 25 LF/ 1.22M x 7.62M |
| Standard Width Tolerance                  | Manufacturer        | +3/4" -0" / +19 mm – 0mm       |
| Standard Length Tolerance                 | Manufacturer        | + 1% - 0                       |
| Standard Thickness Tolerance              | Manufacturer        | + 0.6 mm                       |

Surfaces Install: Flat Hard Surface, Indoors

Shipping: Shrink wrapped on pallets, ships via freight delivery.

Greatmats.com  
117 Industrial Ave  
Milltown, WI 54858  
Toll free: 877-822-6622

Direct voice: 715-653-6100  
Fax: 715-825-4928  
info@greatmats.com  
Revised 10/2024