



Sterling Walkway Pad

Product Specifications

PHYSICAL DIMENSIONS

Size	Thickness	Weight Lbs each	Pcs/ Pallet	Pallet Weight (incl. pallet)	Pallet Height (incl. pallet)
24" x 24"	2.0" Standard	24.6	90	2,304 Lbs	36.0"

PHYSICAL PROPERTIES

Test Description	ASTM Ref.	Results	Test Lab
Freeze Thaw	C67	No change	Element
Rubber Deterioration/Air Oven	D573	No change	Element
Abrasion Resistance	C501	205	DTL
Density	D3676	817 kg/m ³	DTL
Slip Resistance	E303	44 Wet/51.25 Dry	QAI Laboratories
Slip Resistance	D2047	0.533	QAI Laboratories
Tensile Strength	D412 (Mpa)	0.661	DTL
Elongation at Break	D412	68.5%	DTL
Tear Strength	D624 (kMn)	2.2	DTL
Peak Tear Load	D624 (N)	51	DTL
Flammability	D2859	Pass	DTL

Shipped on pallets via freight delivery

FEATURES:

- High density wear layer withstands the toughest weather
- Patented tile-locking system connects the tiles together
- Built-in pedestal design provides drainage
- Designed for high traffic areas
- Economical roof walkway option
- 100% recycled rubber
- Maintenance free

WARRANTY:

1 Year limited warranty against manufacturing defects

Greatmats.com
117 Industrial Ave
Milltown, WI 54858
877-822-6622
info@greatmats.com
Revised 8/2024