



# Greatmats Pet Turf Choice Per LF

## Product Specifications

Sku: OS32A

**Roll Size:** 15 foot wide x 1-1/4 inch thick  
**Surfaces Install:** Glue down on flat hard surface, tape seams, turf stakes  
**Shipping:** 1 roll per standard 4x4 ft pallet

Finish Fabric	English System		ASTM Standards
Nominal Specification	Value	Units	Method
Pile Height(Nominal)	1.25	inches	D-5823
Face Weight	58	oz/yd <sup>2</sup>	D-5848
Total Fabric Weight	84	oz/yd <sup>2</sup>	D-5848
Primary Backing Weight	6	oz/yd <sup>2</sup>	D-5848
Secondary Coating Weight	20	oz/yd <sup>2</sup>	D-5848
Tuft Bind	>8	lbs.	D-1335
Grab Tear Strength(Average)	>200	lbs.	D-5034
Lead Content	<50	ppm	F-2765
Total Yarn Linear Density	15,800	Denier	D-1577
Elongation to Break	>60	%	D-2256
Yarn Breaking Strength	>19	lbs.	D-2256
Yarn Melting Point	248	F°	D-7138
Machine Gauge	3/8	inches	D-5793
Flammability	Pass		D-2859
Water Permeability	>32	in/hr	DIN 18-035
Fabric Width	15	ft	None

### MATERIALS

Primary Yarn Polymer	Polyethylene
Yarn Cross Section	Omega / "S" Shape
Standard Color	8215 Field/Apple
UV Stabilized	Yes
Fabric Construction	Tufted
Secondary Yarn Polymer Thatch	Polyethylene
Secondary Yarn Color	Green/Tan
Primary Backing	Dual Polypropylene
Coating Type	Polyurethane
Polyethylene Yarn Denier / Ends	10,800/6
Texturized Thatch Denier /Ends	5,000/8
Sustainability	Recyclable
Warranty Period	15 years